

WIRE FREE NEON FLEX SERIES


LZ-21512-HN-2835-120P




TECHNICAL DATA

INPUT VOLTAGE	220V AC
IP CODE	IP66
LED TYPE	SMD2835
SERVICE LIFE	3 Years
CRI	>80
BEAM ANGLE	120°
DIMENSION	W15*H14MM
BENDING DIRECTION	top bend

POLAR AND CONE DIAGRAM




PHOTOMETRIC OF 1M STRIP



PRODUCTION OPTIONS

Item No.	Input voltage (V)	Power (W)	Color temperature	FPCB width	Luminous Flux	Cutting Possibility (MM)	Max Run length	LED QTY (PCS)	IP GRADE
LZ-21512-HN-2835-120P	220V AC	8.5W/M	2700±100K 3000±150K 4000±200K 6000±250K	8MM	510lm/M 530lm/M 595lm/M 615lm/M	1000	50M	120pcs	IP66

Mounting Accessories



Flat Mounting Clip/aluminum Profile



Flexible Mounting Chain



Middle connector




Front connector



End cap & Plastic clip

BENDING DIAMETER



RoHS CE facts®



PRODUCT FEATURES

- Consistency ,dot-free illumination
- Automatic system ,high production capacity
- High quality circuit for stable and reliable performance.
- Unique extrusion process and electronic design can be flexible bended in horizontal way

- Working temperature:-10~40°C

SPECIFICATION

POWER CONSUMPTION

HIGH COLOR RENDERING INDEX

SUPER HIGH LIGHT OUTPUT



Beam Angle 120°
Flame Resistant
IP Protection
Solvent Resistant
IK08 Protection
UV Resistant
Warranty 3 YEAR
Saltwater Resistant
AC220V