

EMBER - 1



Mini recessed luminaire EMBER for floor/ground/wall and ceiling installation, perfect choice for accent spot lighting solutions, glare-free lighting, superior visual comfort with the baffle and honeycomb structure, good range of beam options, no heat build-up at the light beam, without any visible screws, stainless steel body, tempered safety glass, 316L stainless steel ring, corrosion resistant, low voltage constant current power supply (350mA) to be ordered separately, optional model in 24Vdc also available..

Mini apparecchio da incasso EMBER per installazione a pavimento/terra/parete e soffitto, scelta perfetta per soluzioni di illuminazione spot d'accento, illuminazione senza abbagliamento, comfort visivo superiore con la struttura a baffle e a nido d'ape, buona gamma di opzioni di fascio, nessun accumulo di calore fascio di luce, senza viti a vista, corpo in acciaio inox, vetro di sicurezza temperato, ghiera in acciaio inox 316L, resistente alla corrosione, alimentatore a bassa tensione a corrente costante (350mA) da ordinare separatamente, optional disponibile anche in versione 24Vdc..

Product information

LZ-24312-E / 1W

Installation / Installazione:	Recessed / Interrato
Material / Materiale:	Die-Aluminum / Alluminio
Front Cover / Verniciatura:	Stainless Steel316L / Verniciatura a polvere
System power(W):	1
Fixture lumen output(lm):	75
System efficiency(lm/W):	75
Led driver / alimentatore	Included / Incluso
Tilt Angle / Angolo di inclinazione:	No

Light source information

Led Typology / Tipo di Led:	COB CREE
Led power consumption (W)	1
Lumen output / Flusso 3000K CRI 80 (lm):	100
Led efficiency (lm/W):	100


Material Accessories

Cable galand	IP-68 Plastic sleeves
Power cable/Cavo di alimentazione	0.5m H05RN-F 2x1.0mm2
Driver / Prodotti per scatola:	12-24V DC



Code composition / Composizione del codice

Model	Power	CRI	RA	CCT	K	Beam °	Color	Cover	Dimming
LZ-24312-E	1W	80	>82	SDCM 3	30	3000	20	BK White	Clear On-Off
		90	>92	SDCM 3	40	4000	SL Black	Frosted	



Accessories



Connector IP68
A62591



A60212