

ALTER- 12



Surface-mounted square wall light with single or dual side illumination with the functionality of changing beam angle manually, discreet and integrative design to use with architectural surroundings, glare-free light and enhanced visual comfort, body made of aluminum, specially designed narrow beam optical accessory to create a slim beam of light, different body color choices, the ideal solution for building façade, exterior walls, entrance zones.

Lampada da parete quadrata a montaggio superficiale con illuminazione singola o doppia con la funzionalità di modifica manuale dell'angolo del fascio, design discreto e integrato per l'utilizzo con l'ambiente architettonico, luce priva di abbagliamento e comfort visivo migliorato, corpo in alluminio, ottica a fascio stretto appositamente progettata accessorio per creare un fascio di luce sottile, diverse scelte di colore del corpo, la soluzione ideale per facciate di edifici, pareti esterne, zone di ingresso..

Product information

LZ-28112-12 BK/WH

Installation / Installazione:	Surface / Superficie
Material / Materiale:	Die-Aluminum / Alluminio
Front Cover / Verniciatura:	Die-Aluminum / Alluminio
System power(W):	12
Fixture lumen output(lm):	960
System efficiency(lm/W):	80
Led driver / alimentatore	Included / Incluso
Tilt Angle / Angolo di inclinazione:	Yes,manual

Light source information

Led Typology / Tipo di Led:	SMD CREE/OSRAM
Led power consumption (W)	12
Lumen output / Flusso 3000K CRI 90 (lm):	120
Led efficiency (lm/W):	100

Material Accessories

Cable galand	IP-65 copper and nickel coated
Step tempered glass/Gradino in vetro temperato	T=12MM,Loading capacity: >130kg
Power cable/Cavo di alimentazione	0.5m H05RN-F 2x1.0mm2
Driver / Prodotti per scatola:	12-24V DC/AC110-277V

Code composition / Composizione del codice

Model	Power	CRI	RA	CCT	K	Beam °	Color	Cover	Dimming		
LZ-28112	12W	85	>85	SDCM 3	30	3000	0-120	WH	White	Clear	On-Off
		90	>90	SDCM 3	40	4000	BK	Black			

Material composition / Composizione del material

